



Galvashield® Tidal Jacket

Galvanic Jacket System with Zinc Mesh Anodes

DESCRIPTION


The Galvashield Tidal Jacket galvanic protection system, formally available as Galvanode® Jacket with Zinc Mesh, is designed to provide a low-cost reliable method of extending the service life of corroding piles in tidal saltwater environments. The Galvashield Tidal Jacket system is comprised of galvanic zinc mesh anodes inside a fiberglass-reinforced polymer (FRP) stay-in-place form. After the anodes and jackets are placed around the structure, the annular space is filled with portland cement concrete or mortar. Unlike traditional FRP or concrete jackets, epoxy grouted jackets and wraps, the Galvashield Tidal Jacket provides ongoing galvanic current to address tidal zone corrosion. The system is self-powered and regulates its current output according to the corrosion rate of the steel and its operating environment. Galvashield Tidal Jackets use high-purity zinc mesh anodes. The open-bottomed form allows salt water to saturate and activate the zinc mesh inside the jacket. Silver Bullet® Bulk Aluminum Anodes are typically used for supplemental protection below mean low tide. The Silver Bullet Al Anode has been specifically engineered for use with our Galvashield® Jacket Systems for concrete and steel piles to provide improved performance compared to standard bulk zinc anodes while also being more environmentally friendly to marine life.

To protect pile sections above the tidal zone, Vector recommends the use of Galvashield® Tidal Plus Jackets or Galvashield® DAS Jackets.

The Galvashield Tidal Jacket system is simple to install, and most work can be completed while the structure remains in service. The system requires no maintenance and restores concrete loss due to steel corrosion and concrete spalling in one operation. Galvashield Tidal Jackets can be supplied as round or square jackets with custom lengths suited for the project.



Galvashield Tidal Jacket provides protection to pile section in the tidal zone



APPLICATIONS

- Tidal zone protection for marine piles
- Saltwater exposure
- Prestressed concrete piling
- Steel H piles
- Not recommended for use on piles in freshwater.
- Not recommended for protection of marine pile above the high tide line.

** As with all galvanic protection systems, service life is dependent upon a number of factors including reinforcing steel density, concrete conductivity, chloride concentration, humidity, temperature and anode mass.*

FEATURES AND BENEFITS

- **Low maintenance** - requires no external power source or system monitoring.
- **User friendly** - repair spalled concrete and provide lasting protection in one step. No costly electrical work required.
- **Site support** - on-site training and technical service available from factory-trained cathodic protection technicians.
- **Measurable** - anode performance can be easily monitored if required.
- **Long Lasting** - 10 to 35+ year service life* as required.
- **Minimal downtime** - system can be generally installed without major disruption of operations.
- **Environmentally friendly** - aluminum bulk anodes are not considered toxic to marine life by the EPA.

SPECIFICATION

Contact Vector Corrosion Technologies for assistance in developing job-specific specifications.

HOW IT WORKS


When two dissimilar metals are coupled together in an electrolyte, the metal with the higher potential for corrosion (more electronegative) will corrode in preference to the more noble metal. In concrete applications, the zinc anodes in Galvashield Tidal Jackets will corrode in favor of the reinforcing steel, thus providing corrosion protection.





Galvashield® Tidal Jacket

Galvanic Jacket System with Zinc Mesh Anodes



INSTALLATION INSTRUCTIONS

Installation of the Galvashield Tidal Jacket system can be accomplished with relative ease. The first step is to remove any deteriorated concrete with pneumatic hammers and any marine growth (if applicable) using methods approved by the engineer. Once all loose concrete has been removed, the column is prepared by grit or hydro blasting to clean the concrete and removing all corrosion products from the steel. An electrical connection must be made to the reinforcing steel that is to be protected. If no exposed steel is present, a concrete excavation will

be required to make the reinforcing steel connection. In order for the system to work properly, the steel reinforcement must be electrically continuous to be protected. If specified, the bulk aluminum anode is installed below the low tide line. To monitor the system, all wiring from the zinc anodes and the bulk anode is run up inside the jacket into the junction box.

The Galvashield Tidal Jacket system is installed with a fiberglass jacket assembly with tongue and groove joint(s). The jacket is set on a temporary bottom form and is positioned around the pile and the zinc anodes.

To complete the installation, the Galvashield Tidal Jacket is braced and filled with approved cement-based grout or concrete to completely fill the annular space. Once the grout is cured, the lead wires from the anode in the jacket, bulk zinc anode and reinforcing steel are connected, and the system becomes immediately operational. The continuous flow of current from the zinc anodes provides galvanic corrosion protection to the reinforcing steel.

PRECAUTIONS

Galvashield Tidal Jackets may be part of an overall structure rehabilitation program to extend the service of life of corroding columns and piles. Where structural damage exists, consult a structural engineer.

Galvashield Tidal Jackets may be used in conjunction with Vector’s extensive line of galvanic corrosion protection products to protect other portions of the structure. For more information on corrosion mitigation strategies and options, contact Vector Corrosion Technologies at Vector-Corrosion.com/contact-us.

HEALTH AND SAFETY

Portland cement concrete and mortar should be handled with suitable gloves and other personal protective equipment in accordance with standard procedures for handling cementitious materials.

ABOUT VECTOR

Vector Corrosion Technologies takes pride in offering technically advanced, cost-effective corrosion protection solutions to extend the service life and improve the durability of concrete and masonry structures around the world. Vector has earned numerous project awards and patents for product innovation and is committed to a safe, healthy and sustainable environment. For additional information or technical support, please contact any Vector office or our extensive network of international distributors.

Rev. January, 2023

Canada

Winnipeg, MB
 Phone: (204) 489-9611
info@vector-corrosion.com

United States

Lexington, KY
 Phone: (813) 830-7566
info@vector-corrosion.com

Europe

Cradley Heath, UK
 Phone: (44) 1384 671 400
infoEU@vector-corrosion.com

Middle East

Dubai, UAE
 Phone: +971 50 659 7322
infoME@vector-corrosion.com

Galvashield, Silver Bullet, Vector and the Vector logo are registered trademarks. Patents: US and international patents pending. © 2023 Vector Corrosion Technologies.

